

Supplement of Saf. Nucl. Waste Disposal, 1, 133–135, 2021  
<https://doi.org/10.5194/sand-1-133-2021-supplement>  
© Author(s) 2021. CC BY 4.0 License.



*Supplement of*

## **Large-scale testing of a sandwich shaft-sealing system at the Mont Terri rock laboratory**

**Klaus Wiczorek et al.**

*Correspondence to:* Klaus Wiczorek ([klaus.wiczorek@grs.de](mailto:klaus.wiczorek@grs.de))

The copyright of individual parts of the supplement might differ from the article licence.

Supported by:



Federal Ministry  
of Economics  
and Energy



Schweizerische Eidgenossenschaft  
Confédération suisse  
Confederazione Svizzera  
Confederaziun svizra



Interdisciplinary  
research symposium  
on the safety of nuclear  
disposal practices


on the basis of a decision  
by the German Bundestag

# Large-scale testing of a Sandwich shaft sealing system at the Mont Terri rock laboratory

Klaus Wieczorek, Katja Emmerich, Rainer Schuhmann, Jürgen Hesser, Markus Furche, David Jaeggi, Senecio Schefer, Jan Aurich, Juan Carlos Mayor, Simon Norris, Ken Birch, Manuel Sentis, José Luis García-Siñeriz, Franz Königer, Uwe Glaubach, Christopher Rölke, Ralf Diedel

# The Sandwich sealing system

- Structure: alternating **sealing segments (DS)** of binary mixture of bentonite and **equipotential segments (ES)** for homogeneous hydration
- Advantage: seal bypass and fingering as well as high hydraulic loads are absorbed, seal element re-saturation is more homogeneous
- Patent 2002 (held by KIT-CMM)
- Functional demonstration in semi-scale experiments
- A **large-scale test** taking into account the interaction with the host rock was planned in an international pre-project (2017-2019)
- In-situ implementation was started at the **Mont Terri Rock Laboratory** in 2019 (project **Sandwich-HP**)



# Sandwich-HP: objectives and organization




## Objectives




- Demonstrate the **feasibility of installation**
- Investigate the **re-saturation process**
- Qualify **measurement and monitoring techniques**
- Assess the **sealing effectiveness** (at a later stage of the experiment)

**Partners:** KIT-CMM, GRS, BGR, Swisstopo, Enresa, ENSI, NWMO, RWM, TUBAF

**Contractors:** Amberg, CIEMAT, ISU, IBeWa, IfG, SSKG, Schützeichel, Solexperts, Glözl, VSH



# Test site and configuration





**Shaft 2** installed 1-1.5 years later: pronounced EDZ, modified configuration

# Rock mass instrumentation and response to shaft sinking




Interdisciplinary research symposium on the safety of nuclear disposal practices



Rock mass instrumentation was performed between August 2019 and March 2020.


- Minipiezometers for pore pressure measurement
- Flat cells for stress monitoring
- Boreholes for seismic and geoelectric measurements



# Shaft sinking and related work

August – November 2020

- Drilling and lining of inclined **feeding boreholes**
- **Shaft sinking by core drilling** : Drilling of both shafts within 11 weeks
- Installation of **wire mesh support** and ladders
- Installation of **pressure chamber** at shaft bottom
- **Permeability** measurements on shaft contour (surface packer), **seismic** measurements
- Installation of electrodes for **electric resistivity tomography** (water content)



# Emplacement of sealing system and shaft instrumentation


November – December 2020

Materials emplaced in about decimeter layers and compacted

- **Sealing segments:** pillows and crushed pillows of Calcigel (German Ca-bentonite)
- **Equipotential segments:** fine-grained quartz sand

Instrumentation and cables embedded in the material

- ERT electrode rings / rod TDR (shaft wall)
- TAUPE TDR (water content)
- Water pressure
- Relative humidity / temperature
- Radial stress (shaft wall) and vertical stress
- Axial displacement



# Installation of plug and hydration system

January – May 2021



Interdisciplinary  
research symposium  
on the safety of nuclear  
disposal practices






# Water ingress / cable leakages (August 2021)

- 11 August (after injection pressure increase from 5 to 8 bar): the **water tank emptied into the shaft** and the pressure was lost
- Afterwards, water found in pore pressure sensor cables and ERT electrode cables
- Explanation: Water bypassed DS1 (possibly via contour) and reached sensors with untight cables
- Capturing bypassing water is just the **functionality of the Sandwich seal!**
- All ERT and pore pressure cables sealed using connection boxes filled with resin (effective if the cable insulation withstands the inside water pressure – has been tested)
- Hydration will be resumed in November 2021 with a first pressure step




# Sensor reaction to water ingress


TAUPE TDR




S7h  
ES2



S6h  
ES1  
bottom



S10h  
ES5  
top



S8h, S9h  
ES3, ES4

# Lab testing (Scale transition)


Semi-technical scale  
d=0.8 m; h=1.45 m




## Objectives

- Functionality under fluid inflow pressure up to 100 bar
- Development of binary mixture of bentonite pillows and granular bentonite material (GMB) for DS (pillow geometry, compaction method for powdered and granular bentonite, grain size distribution of GBM)

Oedometer  
d=0.036-0.10 m; h=0.012-0.02 m




MiniSandwich  
d=0.09 m; h=0.12 m



- Characterization of HMC behavior (hydration, swelling pressure, permeability, ion transport, cation exchange) of two national Ca-bentonites for different dry densities and initial hydration state

## Mineralogical/chemical analyses




# Model simulation

Three teams (BGR, ENSI, GRS) performing comparative and complementing simulations

Scoping calculations (already performed in the pre-project)

Interpretative hydromechanical (HM) simulations

- Needed for the evaluation and interpretation of the in-situ experiment
- Require suitable calibrated material models, good knowledge of boundary conditions, and an adequate geometrical representation
  - Model calibration using existing lab tests (e.g., MiniSandwich, swelling pressure tests)
  - In-situ measurements to obtain actual conditions (e.g., stress state, pore pressure)
  - Geometry and model complexity adapted to specific question



# Current status and next steps



## Status

- In-situ experiment is **about 1 year delayed**, due to Covid and cable tightness issues
- Laboratory experiments and modelling run as planned

## First results

- Shaft sinking and **sealing system installation** proved successful
- Sandwich **sealing system shows expected function**, sensors work satisfactorily
- Special care required with respect to sensor cable tightness – testing instead of producer information

## Next steps

- Resume hydration in Shaft 1 with stepwise pressure increase
- Plan Shaft 2 installation
- Proceed with lab experiments and modelling

# Thank you!



## Any questions?

Supported by:



Federal Ministry  
of Economics  
and Energy

on the basis of a decision  
by the German Bundestag

The Sandwich experiment is funded by the German Federal Ministry for Economic Affairs and Energy under contract 02E11799 A+B.