



Supplement of

Concretisation of host-rock-dependent canister concepts through the development of a consistent but variable multi-barrier system for the future engineered barrier system

Thomas Hassel

Correspondence to: Thomas Hassel (hassel@iw.uni-hannover.de)

The copyright of individual parts of the supplement might differ from the article licence.

> Concretisation of host-rock-dependent canister concepts through the development of a consistent but variable multibarrier system for the future engineered barrier systems

Funded by:



Bundesministerium für Umwelt, Naturschutz und nukleare Sicherheit Dr.-Ing. Thomas Hassel



safeND2023 (13.-15. September 2023, Berlin Café Moskau)

Förderkennzeichen: 02E11849A-J




ElaBeMa Förderkennzeichen: 02E12092

Present situation in the site selection process

THOMAUSKE, B. (2023). Ist das Standortauswahlverfahren gescheitert? Auswahl von Endlagerstandorten für hochradioaktive wärmeentwickelnde Abfälle? *Atw. International Journal of Nuclear Power*, vol. 68/3 pp. 7-22.

The site selection process in Germany failed because the design of the process and the safety of the process cannot be reconciled. As part of an amendment, Thomauske suggests carrying out a cross-host rock comparison before evaluating sub-areas.



RÖHLIG, K.J. (2023). Zum Zeitplan des Standortauswahlverfahrens für die Endlagerung hoch radioaktiver Abfälle in Deutschland. *Atw. International Journal of Nuclear Power*, vol. 68/4 *pp.* 52-61.

Too tight a time limit as well as long extensions in the process pose the risk of non-safety-oriented decisionmaking behavior. There is little potential for acceleration until a procedural change is made, but the change in the law must begin quickly.






Institut für

Werkstoffkunde



What measures can be taken to counteract a further delay in the final disposal of highly radioactive waste?

Are there tasks that can be decoupled from the host rock issue and can therefore be addressed before this decision is made?



Source: BGE GmbH Workshop des Planungsteams Forum Endlagerplanung; Vorstellung des Rahmenterminplans bis zum Vorschlag für Standortregionen Online-Veranstaltung, 13.01.2023, Translation added by the author!








1000 444

500 n



Interim storage: Licenced for 40 years as of first packaging / storage of cask, e.g.1994 in Gorleben

- Condition of the fuel elements
- Expiring permits
- Long-term interim storage
- Transportability
- Conditionability



- Three host rock options
- Various geotechnical barrier

2


systems

- Retrievability
- Recoverability
- Conditionability










Host rock: salt rock, clay rock or crystalline rock







Host rock: salt rock, clay rock or crystalline rock






- Container development will only take place after the location and thus the host rock have been decided
 → Danger of delay?
- From now on, three equivalent complete container systems will be designed, planned, constructed and implemented in parallel → Costs and resources?
- Defined requirements for the container must be defined, although one cannot know whether these actually exist at the future location → Depth, water, etc.?
- A change of direction in a late phase of site selection is no longer easily possible when the host rock changes
 see change of direction in Switzerland!
- Production capacities can only be built up after the location decision has been made → Pre-programmed bottleneck for 10.000 to 20.000 containers?
- Number of containers can be optimally designed → Storage space required!







Host rock: salt rock, clay rock or crystalline rock




Consequence approach 2



- The highly radioactive inventory is known → Burnup and heat generation!
- The quantity of the waste is known -> Design requires definition of criteria!
- Shape and dimensions as construction data are available -> BE, special fuels and vitrified molds!
- Radiological requirements are already defined → Dose rate on the surface!
- Material decisions can be made using the international state of the art -> SKB/ POSIVA/ NAGRA!
- Partial approval procedures can start early → Process flow!
- Production capacities available quickly
 → No production bottlenecks!
- Larger number of containers for target host rock → Safety surcharges!
- The long-term stability part can be handeld after the decision has been made → time, costs!







Methodical approach of design thinking:

Basic idea:

Design thinking is about designing innovations and creative solutions to complex problems.

Possibilities:


There are no limits to the range of applications of design thinking. It can be applied to products and services as well as to the development of concepts for entrepreneurial or social issues.

Functional scope:

Design thinking is as much a collection of methods as it is a way of thinking and can be defined differently depending on the application. Techniques and tools enable a systematic approach.

Acceptability:

Openness to results, allowing for mistakes, the courage to fail and the willingness to learn from failure form the necessary inner attitude and fit exactly into the StandAG's objectives.









The classic design thinking process is divided into two main phases:

Analysis und Synthesis.

The two main phases can be divided into six further sections:


- 1. Understand
- 2. Observe
- 3. Define point of view
- 4. Find ideas
- 5. Develop prototype
- 6. Testing





Example of application










Example of application










Example of application









This approach is not fully optimized to a host rock, so all design criteria must be based on conservative boundary conditions:

- allowable heat generation as a general boundary condition
- permissible dose rate at the surface of the vessel
- permissible mechanical load worst case oriented
- self-shielding or overpack?
- Line storage or vertical in boreholes?

•


The procedure must be designed as a transparent learning process to bring society along and achieve acceptability.

However, the number of containers to be stored can thus be determined at a very early stage so that, for example, production capacities can be created in the market.



Interpretation of the POLLUX Approach





- Pollux family as historical german canister system
 - 1. Pollux 3: Fuel rods (WG clay rock)
 - 2. Pollux 9: Ingot molds (WG salt rock)
 - 3. Pollux 10: Fuel rods (WG salt rock)



Pollux-Prototype-Container (Source: "Direkte Endlagerung", Kernforschungszentrum, Karlsruhe 1990)




Storage device for Pollux prototype container (Quelle: Besuch BGE Peine 2023)



© Leibniz Universität Hannover, IW, Prof. Dr.-Ing. Hans Jürgen Maier, Dr.-Ing. Thomas Hassel Page 16 | 13 September 2023

Interpretation of the POLLUX Approach









Example: Sweden (SKB)/Finland (POSIVA)








- 1. Molded tubes made of unalloyed steel to accommodate the fuel elements
- 2. Casting of these tubes with cast iron (GGG40)
- 3. Inner steel cover screwed
- 4. Enclosing of the inlet with a copper cladding
- 5. Seal welding of Cu cladding and Cu cover

Source: Raiko, H., Sandström, R., Ryden, H., and Johansson, M. 2010. Design analysis report for the canister. Technical Report TR-10-28. Swedish Nuclear Fuel and Waste Management Co.






Finland - only licensed repository in the world - crystalline rock



Kupfer-Bentonitschicht und Felsschicht von Brennstab Kanister bis zu 500m ummantelung Tunnelaufschüttung £1

Onkalo: Schritte der Endlagerung









Conclusions

- Extending the site selection phase carries:
 - the risk of overburdening future generations.
 - the risk of losing the safety-oriented approach by extending the interim storage phase.
 - overall, the risk of failure due to loss of acceptance.
- The application of modern methods enables:
 - the advancement of development steps in cask development without having to develop a complete cask system for each host rock.
 - to quickly complete and manufacture the repository cask after the host rock decision has been made.
 - to use the phase of the repository construction consequently for the cask production and to work ahead.



Interdisziplinäres Forschungssymposium für die Sicherheit der nuklearen Entsorgung

Institut für Werkstoffkunde Prof. Dr.-Ing. Hans Jürgen Maier

Concretisation of host-rock-dependent canister concepts through the development of a consistent but variable multibarrier system for the future engineered barrier systems

Dr.-Ing. Thomas Hassel

safe

Funded by:



Bundesministerium für Umwelt, Naturschutz und nukleare Sicherheit Volkswagen**Stiftung**Niedersächsisches Ministerium
für Wissenschaft und Kultur

safeND2023 (13.-15. September 2023, Berlin Café Moskau)

Förderkennzeichen: 02E11849A-J



ElaBeMa Förderkennzeichen: 02E12092